



Engineered with



**DESCRIPTION**

# HinderRUST

## Rust Inhibitor and Lubricant

HinderRUST is a solvent-free and non-hazardous rust stopper and lubricant engineered for surface film management.

**R2.0 The Rust Protector:** Provides temporary surface protection for metal parts that need protection after fabrication, or during storage and transportation. Removable by washing to allow for final finishing.

**S4.0 The Rust Stopper:** Extreme surface adhesion and wetting across the surface and mounted parts allows for self-repairing, rust protection, and lubrication.

**HV100 The Rust Shield:** Substance slowly self-polymerizes over time and provides added protection in extreme weather exposure. Great for use as a protective undercoating on vehicles, plus earth moving and excavation equipment.

**TYPICAL APPLICATIONS**

**R2.0 The Rust Protector**

- Machined parts
- Castings
- Stampings

**S4.0 The Rust Stopper**

- Equipment maintenance
- Battery terminals and electronics
- Frees up frozen joints and fasteners
- Apply pre-assembly to stop corrosion
- Tools and weapons protection
- Protect and lubricate wire rope cables

**HV100 The Rust Shield**

- Undercoating on vehicles, excavation, earth moving and industrial equipment
- Protection in extreme weather conditions

**TYPICAL PROPERTIES**

HinderRUST is a translucent tan liquid with a mild petroleum odor. It is solvent-free which means it is safe for users, non-flammable, and can be used in confined spaces.

% VOC – ASTM D2369

R2.0: 8.6%

S4.0: 3.0%

HV100: 2.0%

Viscosity – ASTM D445

@40°C @100°C

R2.0: 90 cSt; 18 SUS

S4.0: 119 cSt; 25 SUS

HV100: 111 cSt 19 SUS



Available sizes for HinderRUST:

- 4 oz. with dauber (S4.0 only)
- 8 oz. BoV Pinpoint Stream Can (S4.0 only)
- 11.5 Aerosol Spray Can (S4.0-ASC)
- 5 gallon

- 8 oz. squirt bottle
- quart
- gallon
- 55 gallon



Winona, MN • Made in the USA

www.fluoramics.com

1-800-922-0075

1-507-205-9216

Fax: 507-474-4585

**HinderRUST®**

Engineered with

**Tufoil®**  
TECHNOLOGY

# HinderRUST

## Rust Inhibitor and Lubricant

### APPLICATION DETAILS

### STORAGE/SHIPPING/ HANDLING

See directions for use below.

No special handling required.

HinderRUST is a very safe product. Wash hands after use. Keep out of eyes.

### Use HinderRUST on . .

- Shop Tools
- Nuts and Bolts
- Near-water Environments
- Storage of Molds & Dies
- Battery Terminals
- Wire Rope Cables
- Forklifts
- Swing Chains
- Conveyors
- Steering Cables
- Spare Parts Storage
- Gardening Tools
- Wiring & Harnesses
- Wheels
- Chain Drives
- Gardening Tools
- Trailers & Hitches
- Locks & Hinges
- Firearms
- Yard Art
- Vehicle Underbodies

### DIRECTIONS FOR USE:

1. Shake occasionally.
2. Simply apply by brushing or spraying on to new or rusty metal. No prep is needed for rusty metal.
3. Coat the surface with a thin even layer. HinderRUST will wet and spread to a thin, glossy layer. Will penetrate between layers of metal and stop corrosion. HinderRUST may be applied to wet or dry metals.
4. On wire ropes, brush or spray on the surface, HinderRUST will soak and spread to the center of the cable.
5. HinderRUST is not conductive so it is safe to brush directly on to electrical connections, cable ends, and battery terminals.
6. Parts/components can be put back in use immediately.
7. HinderRUST starts protecting and lubricating the surface upon application.
8. An annual maintenance program for reapplication is recommended if constant, repeated exposures to water sprays greater than a rainfall are to occur.

Thread Sealants Tufoil® Technology HinderRUST Oxygen-Safe Greases & Pastes

 **Fluoramics, Inc.**

Winona, MN • Made in the USA

www.fluoramics.com

1-800-922-0075

1-507-205-9216

Fax: 507-474-4585