

Product Description

Rust-Stopping Lubricating Oil stops rust in its tracks while providing lubrication. It is engineered with a blend of unique chemistries that allows it to travel beyond the area to which it is applied.

Features

- High dielectric strength – will not conduct electricity
- Non-toxic, non-hazardous, non-flammable, solvent-free – will not evaporate away!
- Compatible with today's engineered plastics and rubbers
- PFAS-free

Benefits

- Deep penetration into areas that cannot be reached
- Robust packaging paired with a dropper tip designed for precise application
- Water and moisture displacing
- Compatible with today's engineered plastics and rubbers



Applications

- | | | |
|-------------------------------------|------------------|--------------------------|
| ▪ Machine and equipment maintenance | ▪ Fan motors | ▪ Lug nuts |
| ▪ Exterior locks and hinges | ▪ Power tools | ▪ Padlocks |
| ▪ Slides | ▪ Pivot points | ▪ Window hardware |
| | ▪ Nuts and bolts | ▪ Wiring and electronics |

Health and Safety

Rust-Stopping Lubricating Oil is a very safe, solvent-free product. This product is not classified as hazardous according to OSHA 29 CFR 1910.1200 and WHMIS. Not hazardous under the consumer product safety regulations. See the Safety Data Sheet for additional information.

Storage, Shipping and Handling

Always keep the unused product in the original container, tightly closed. This product is DOT-classified as non-hazardous and can be shipped by air with no shipping restrictions. See the Safety Data Sheet for additional information.

Specifications and Approvals

Test	Rating
Physical State	Liquid
Color	Translucent Tan
Odor	Slight - negligible
California Air Resources Board (CARB) Compliant	Yes
VOC ASTM D2369 EPA test 24	Liquid: 1.05%
LVP-VOC of Mixture	Liquid: 0.21% Aerosol Package: 22%
Flammable OSHA CFR 29 910.106	+238°C (+460°F)
Flashpoint ASTM D92	No
Vapor Pressure	<0.1 mmHg at +20°C (0.002 psi @ +68°F)
Torque K-Factor (Lubricated Bolt)	Zinc Plated Bolt: 0.128 Stainless Steel: 0.362

Test	Rating
Ecotoxicity	Not harmful
Biodegradation	Inherently biodegradable
Soluble in Water	No
Salt Fog Test ASTM B117	Direct Dripping Exposure: 300 to 500 hours Undercover +87,000 hours to indefinitely
Specific Gravity @ 150°C (60°F)	0.855 g/cm ³ (0.512 oz/in ³)
Kinematic Viscosity ASTM D445	119.5 cSt @ +40°C (+104°F) 24.87 SUS @ +100°C (+212°F)
Dielectric Breakdown Voltage ASTM D877-A	Liquid: 18.20 kV
EP Properties Falex – True Load Failure ASTM D3233	Liquid: 358 kgf (790 lbf)
Four Ball Wear ASTM D4172 40 kgf	Liquid: 0.483 mm (0.018 in)
Weld Through Approved WTTI	Yes

How to Apply

Application Methods: Shake before use. Gently squeeze the bottle and apply it to the area needing rust-stopping lubrication. Reapply as needed.

Packaging

Part No.	Size	Container	Case Quantity
9644383	16.5 mL (0.557 fl oz)	Dropper Tip	48

