



Engineered with



DESCRIPTION

Rust-Stopping Lubricating Oil

Rust-Stopping Lubricating Oil is engineered with both HinderRUST and Tufoil Technology. It cleans, lubricates, and protects while providing extreme surface adhesion and wetting across the surface and mounted parts. Weld-through approved and stops rust and corrosion.

HinderRUST is a solvent-free and non-hazardous synthetic rust stopper and lubricant engineered for surface film management.

APPLICATIONS

Rust-Stopping Lubricating Oil works great on:

- Machine and equipment maintenance
- Hinges
- Locks
- Power Tools
- Bike chains
- Pivot points



PROPERTIES

HinderRUST is a translucent tan liquid with a mild petroleum odor. It is solvent-free which means it is safe for users, non-flammable, and can be used in confined spaces.

Test	Test Method	Rating
Color	--	Translucent Tan
Odor	--	Mild
Viscosity cSt @40° C	ASTM D445	119.5
Viscosity cSt @100° C	ASTM D445	4.9
VOC	ASTM D2369	3%
Dielectric Breakdown Voltage	ASTM D877	18.20 kV
Four Ball Test: Test Scar Diameter	ASTM D4172	0.48 mm
Extreme Pressure Properties	ASTM D3233	790 lbf
Salt Spray Test: 196 Hours	ASTM B117	Pass

PACKAGING/ APPLICATION

Rust-Stopping Lubricating Oil is available in a 12 ml. Pocket Oiler.

APPLICATION DETAILS

Take off cap and tip. Gently squeeze tube to apply.

SHIPPING/HANDLING

No special handling required.

HEALTH & SAFETY

Rust-Stopping Lubricating Oil is a very safe product. Wash hands after use. Keep out of eyes. Refer to Safety Data Sheet (SDS) for more information.